



G6990-19 ATC/TCAS Control Panel

GENERAL SPECIFICATIONS

Dimensions

- 2.235 (height) x 5.735 (width) x 5.0 (depth) inches, excluding rear connectors

Weight

- 2.0 pounds (max)

ATC Code Range

- 0000 to 7777 (Octal)

Electrical Requirements

- Power115 VAC @ 400 Hz, 5 Watts (max)
- Panel Lighting (Incandescent White)5 VAC variable
- Indicator Lighting (Incandescent White) 28/12.5 VDC dimming input voltage

Connectors

- J1 Mating: M83723-75R16247, or equivalent 24 pin connector
- J2 Mating: M83723-75R16248, or equivalent 24 pin connector



G6990-19 ATC/TCAS Control Panel

Color

- Front Panel – Non-reflective Gray FED STD 595b36118
- Knobs – Non-reflective Black FED STD 595b37038
- Front Panel Markings – White FED STD 595b37875 (Futura Medium Condensed font)
- Push Buttons – Non-reflective Black FED STD 595b37038

Compliance

- RTCA/DO-160B (Environmental), RTCA/DO-178A (Software), RTCA/DO-181 (ATCRBS/Mode-S), RTCA/DO-185 (TCAS)
- ARINC 429, ARINC 532, ARINC 572, ARINC 706, ARINC 718, ARINC 720, ARINC 735

Certification

- TSO-C112, TSO-C119
- B737-600/700/800/900

Features

- Dual Mode-S configuration
- Transponder fail indicator (amber)
- Ident function
- Keypad entry for ATC code
- Altitude reporting ON
- Transponder 1-2 selection
- Transponder STBY/AUTO/ON function
- TCAS TA only, TA/RA
- System test function
- ABV/N/BLW function
- Altitude limit range: A = 2,700 ft, B = 7,000 ft
- Built-in-test (BIT) capability
- Non-volatile storage for ATC code
- Modular design provides flexibility for custom layouts
- Modular construction contributes to economical maintenance
- MTBF (Calculated): 15,000 operating hours

Gables Engineering Inc.

247 Greco Avenue, Coral Gables, Florida 33146

Tel: (305) 774-4400 ♦ Fax: (305) 774-4465

www.gableseng.com

Proprietary Information

9/10/12 ♦ Rev. 04